

SS

Body material


Blackened steel or stainless steel

Ball material

Bearing steel or stainless steel

Spring material

Spring steel or stainless steel



Part No.	A	B	Thread size	Body material	Ball material	Spring material	Initiating force (N)	Force for full retraction (N)
12681X	1.5	8	M3	Blackened steel	Bearing steel	Spring steel	3	5
12682T	2.5	10	M4	Blackened steel	Bearing steel	Spring steel	5	8
12683P	3	13	M5	Blackened steel	Bearing steel	Spring steel	7	11
12684W	3.5	15	M6	Blackened steel	Bearing steel	Spring steel	10	18
12685S	5	18	M8	Blackened steel	Bearing steel	Spring steel	30	45
12686Z	6	21	M10	Blackened steel	Bearing steel	Spring steel	30	50
12687V	8	25	M12	Blackened steel	Bearing steel	Spring steel	50	80
12688R	10	28	M16	Blackened steel	Bearing steel	Spring steel	80	165
12689Y	12	35	M20	Blackened steel	Bearing steel	Spring steel	55	95
12690U	1.5	8	M3	Stainless Steel	Stainless steel	Stainless Steel	3	6
12691Q	2.5	10	M4	Stainless Steel	Stainless steel	Stainless Steel	2	4
12692X	3	13	M5	Stainless Steel	Stainless steel	Stainless Steel	7	11
12693T	3.5	15	M6	Stainless Steel	Stainless steel	Stainless Steel	10	18
12694P	5	18	M8	Stainless Steel	Stainless steel	Stainless Steel	15	25
12695W	6	21	M10	Stainless Steel	Stainless steel	Stainless Steel	25	45
12696S	8	25	M12	Stainless Steel	Stainless steel	Stainless Steel	70	105
12697Z	10	28	M16	Stainless Steel	Stainless steel	Stainless Steel	85	140
12698V	12	35	M20	Stainless Steel	Stainless steel	Stainless Steel	60	100